

Printer ID Sheet in order to learn more about the features that makes the panel printer unique

PLUS II

Ultra-Compact Panel Printer

Main Features

- Thermal printing technology 8dot/mm
- Graphic and text printing
- Paper width 58mm
- 50mm paper roll diameter
- "SIXLOAD" paper loading patented system
- Speed > of 50 mm/sec
- TTL, RS232, Centronics and **USB interface**
- Barcodes: EAN8, EAN13, ITF, CODE39, CODABAR
- Fonts: European, International, Portuguese, Nordic
- MTBF > of 800.000 hours
- Sensors: head temperature, paper end and cover open optional
- Dimensions (LxWxH) : 85x57x85.5mm
- Weight: 140gr (without paper roll)



Exclusive Features

- The only with USB on board !
- Double opening of the cover: "comfort" with central key or with "double hook".
- Print on thermal paper or on "linerless" adhesive labels
- Wide range of power supply from 3.3V to 40Vdc (10-32 Vdc for USB model)



Label linerless ready

Double hooks opening

Software Features

- Printing Driver for Win2000/XP/Vista
- Windows CE 5.0 Driver for the new generation of PLC

EASYLOCK innovative fixing system

- reduces assembling time more than 80% !
- allows to adapt PLUS II to any panel thickness
- makes easy and fast printer fixing, without any tools!

Most Common Applications

- Garage equipments
- Medical instruments
- Panel PC and control systems
- Weighing instruments
- Fire alarm controls
- Sterilization equipments
- Taximeters
- Truck tachigraph



Available Versions

- Serial RS232 + USB 10-32V power supply
- Serial RS232 3.3-7V power supply
- Serial RS232 9-40V power supply
- Serial TTL 9-40V power supply
- Parallel Centronics 5V power supply
- Parallel Centronics 9-40V power supply
- TTL parallel 3.3-7V power supply
- Only printing mechanism (no control board)

All versions are linerless

