




HR1250
Anchoa
handheld barcode
scanner



FEATURES

Ergonomic lightweight design.

This ergonomic lightweight scanner fits comfortably in any user's hands to reduce the fatigue of long-time operation, ideally suited for scan-intensive applications.

Cost-effective solution.

The HR1250 delivers aggressive scanning capabilities and excellent user experiences at an attractive price.

Superior decoding performance.

The HR1250 offers an impressive read rate of up to 300 scans per second, helping boost productivity and profitability.

Ecofriendly.

Newland's HR1250-70 operates on 55mA \pm 5mA current only. This means increased energy savings and an ecofriendly business solution.

Application Scenarios

Retail chains • inventory counting • express delivery services • warehouse management • food traceability • healthcare • manufacturing • electricity meter reading and more.

HR1250 Anchoa

handheld barcode scanner

newland-id.com

Performance	Image Sensor	Linear imager		
	Light Source	Red LED (610nm~640nm)		
	Symbologies	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.		
	Resolution	≥4mil		
	Typical Depth of Field	EAN-13	50mm-655mm(13mil)	
		Code 39	55mm-165mm(5mil)	
		Code 128	40mm-495mm(10mil)	
	Scan Angle	Pitch: ±60°; Roll: ±30°; Skew: ±60°		
	Symbol Contrast	≥30%		
	Scan Rate	300 scans per second		
	Interface	USB		
	Physical/ Electrical	Dimensions (L×W×H)	163.0×68.4×58.5mm	
		Weight	130g (USB cable included)	
		Notification	Beep, LED indicator	
Input Voltage		DC5V		
Current		Maximum	<120mA	
		Operating	55mA±5mA	
		Standby	21mA±2mA	
Environmental	Operating Temperature	-20°C~+60°C		
	Storage Temperature	-40°C~+85°C		
	Humidity	5%~95% (non-condensing)		
	ESD	±8 KV (contact discharge); ±10 KV (air discharge)		
Certifications	FCC Part15 Class B , CE EMC Class B			

Specifications are subject to change without notice.

Version: V1.0

Newland EMEA HQ
+31 (0) 345 87 00 33
info@newland-id.com
newland-id.com

D-A-C-H
+49 (0) 6182 82916-16
info@newland-id.de

United Kingdom
+44 (0) 1442 212020
sales@newland-id.co.uk

France
+39 (0) 345 8804096
france@newland-id.com

Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Benelux
+31 (0) 345 87 00 33
benelux@newland-id.com

Turkey
+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Middle East
+39 (0) 345 8804096
middleeast@newland-id.com

Italy
+39 (0) 342 0562227
italy@newland-id.com

South Africa
Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic
+46 (0) 70 88 47 767
nordic@newland-id.com

Iran
+90 (0) 544 538 40 49
iran@newland-id.com