



EM2037V4
OEM scan engine



FEATURES

Superior decoding performance.

No matter what type of barcode is presented, the megapixel camera allows users to scan 1D and 2D barcodes, including very small ones, with impressive speed and ease. In addition to excellent scanning of high-density barcodes, the EM2037V4 also provides the added value of decoding postal barcodes.

Advanced technology.

The EM2037V4 is powered by advanced imaging technology and Newland patented UIMG technology, a computerized image recognition system, can read barcodes printed on paper/plastic or displayed on mobile phones with excellent motion tolerance.

Powerful data editing capability.

The scan engine allows customizing scanned data with ease and provides supporting software to address diverse application needs.

Compact & lightweight design.

Seamless integration of imager and decoder board makes the scan engine very small, lightweight and easy for integration.

Various interfaces.

The EM2037V4 supports USB and TTL interfaces to meet customer needs.

Application Scenarios

Kiosks • ticketing machines • PDA's • tablets and many more.

Performance	Image Sensor	1280 * 800 CMOS		
	Illumination	Red LED		
	Aimer	Red LED		
	Symbologies	2D	PDF 417, QR Code, Micro QR, Data Matrix, Aztec, Maxicode, Chinese Sensible Code, GM Code, Micro PDF417 Code, Code One	
		Postal	USPS Postnet, Royal Mail, KIX Post, Australian Postal, etc.	
		1D	EAN-8, EAN-13, UPC-E, UPC-A, Code 128, UCC/EAN128, I2Of5, ITF-14, ITF-6, Matrix 25, CodaBar, Code 39, Code 93, ISSN, ISBN, Industrial 25, Standard 25, Plessey, Code11, MSI-Plessey, UCC/EAN Composite, GS1 Databar, China Post 25, Code 49, Code 16K	
	Resolution*	≥4mil		
	Typical Depth of Field*	Code 39 (5mil): 70mm-180mm EAN-13 (13mil): 55mm-365mm PDF417 (6.7mil): 55mm-175mm Data Matrix (10mil): 50mm-175mm		
	Min. Symbol Contrast*	25%		
	Scan Angle**	Roll: 360°, Pitch: ±55°, Skew: ±55°		
Field of View	Horizontal 51°, Vertical 32°, Same as FM430 Series			
Mechanical/ Electrical	Interface	TTL-232, USB		
	Operating Voltage	12-pin FPC connector: 3.3-5VDC±5%		
		5-pin connector: 5VDC±5%		
	Rated Power Consumption	916.6mW (typical)		
	Current@5VDC	Operating	179.2mA (typical), 190.9mA (max.)	
		Idle	66.8mA	
	Dimensions	39.5(W)×25.4(D)×20(H)mm		
Weight	9.2g			
Environmental	Operating Temperature	-20°C to 60°C (-4°F to 140°F)		
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)		
	Humidity	5% to 95% (non-condensing)		
	Ambient Light	0~100,000lux (natural light)		
Certifications	FCC Part15 Class B, CE EMC Class B			
Accessories	EVK	Software development board for the NLS-EM2037 V4, equipped with a trigger button, beeper and RS-232 & USB interfaces.		
	Cable	USB	Used to connect the NLS-EVK to a host device.	
		RS-232	Used to connect the NLS-EVK to a host device.	
Power Adapter	DC5V power adapter to power the NLS-EVK with RS-232 cable.			

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

Version: V1.0

**Test conditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp; 2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

*Specifications are subject to change without notice.

Newland EMEA HQ

+31 (0) 345 87 00 33
info@newland-id.com
newland-id.com

D-A-C-H

+49 (0) 6182 82916-16
info@newland-id.de

United Kingdom

+44 (0) 7771 631387
info@newland-id.co.uk

France

+39 (0) 345 8804096
france@newland-id.com

Russia

+31 (0) 345 87 00 33
russia@newland-id.com

Benelux

+31 (0) 345 87 00 33
benelux@newland-id.com

Turkey

+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica

+31 (0) 345 87 00 33
info@newland-id.com

Middle East

+39 (0) 345 8804096
middleeast@newland-id.com

Italy

+39 (0) 342 0562227
italy@newland-id.com

South Africa

Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic

+46 (0) 70 88 47 767
nordic@newland-id.com

Iran

+90 (0) 544 538 40 49
iran@newland-id.com