



**PT60  
Narvalo**  
Windows mobile  
computer

## FEATURES

### Windows CE Operating System.

Built to work with Windows CE, the PT60 Narvalo can support your technology environment perfectly.

### Uninterrupted Productivity.

Equipped with a 3,800 mAh battery, the PT60 Narvalo lasts an average of 10 hours. For scan intensive workdays, a cradle with spare battery charging slot can be used to ensure a full charge is always on hand.

### Stay Connected.

The PT60 Narvalo is equipped with WiFi (802.11b/g/n, 2.4 Ghz) that supports up to 54Mbps. Additionally, it is possible to communicate with other devices through Bluetooth.

### Less Weight, more Comfort.

At only 303g (including battery), this mobile computer brings all day comfort to your operations. Its physical keyboard combined with a crystal clear 3.7 inch touch screen allows workers to navigate the device with ease.

### Effortless out of the Box Experience.

Take the PT60 Narvalo out of the box and get started right away. The device comes ready to use and configuration is quick and simple, minimizing the time needed to set up the devices.



Charging cradle.

### Application Scenarios

Transport and Logistics (Warehouse, Backoffice) • Retail (Warehouse, Backoffice, Store) • Manufacturing (Operational Data Collection) • Healthcare (Patient Care, Laboratory and pharmacy).

# PT60 Narvalo

## Windows mobile computer

newland-id.com

<b>Performance</b>	Processor		Marvell XScale PXA310, 806MHz CPU
	Operating System		Microsoft Windows CE.NET 6.0
	Memory	256MB RAM	
		128MB ROM	
		4GB flash memory for user storage	
Interface		Micro USB 2.0, Battery charging over USB supported	
<b>Physical</b>	Dimensions		166(L) ×73(W) ×26(H) mm
	Weight		303g (including battery)
	Display		3.7" WVGA with backlight TFT touch screen
	Keypad		33 keys (side keys included) with backlight
	Notification		Vibrator, speaker and multi-color LEDs
	Battery	Main	3.7V, 3800mAh rechargeable Li-Polymer battery
		Backup	3.7V, 150mAh rechargeable Li-Polymer battery (supports 50-hour data backup)
	Expected Battery Life		10 hours (1 scan per second)
	Expansion		MicroSD card slot (max. 32GB)
	AC Adapter		Output: DC5V, 1.5A Input: AC100~240V, 50~60Hz
<b>Environmental</b>	Operating Temperature		-10°C to 50°C (-14°F to 122°F )
	Storage Temperature		-20°C to 60°C (-4°F to 140°F)
	Humidity		5% to 95% (non-condensing)
	Static Discharge		±15 kV (Air discharge), ±8 kV (Direct discharge)
	Drop		1.2m
	Sealing		IP54
<b>Barcode Scanning</b>	1D Barcode	Laser (≥4mil) CCD (≥4mil)	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, etc.
	2D Barcode	CMOS(≥5mil)	All major 1D symbologies, PDF417, QR Code, Data Matrix, Maxicode, Aztec, etc.
<b>Wireless</b>	WLAN RADIO		IEEE 802.11 b/g/n, security supports EAP, WEP, WPA, WPA2
	WPAN RADIO		Bluetooth Class II V2.0
<b>Certifications</b>			FCC Part15 Class B, CE EMC Class B, CCC
<b>Accessories</b>			Cradle, battery, AC adapter, USB cable, stylus

\*Specifications are subject to change without notice.

**Newland EMEA HQ**  
+31 (0) 345 87 00 33  
info@newland-id.com  
newland-id.com

**D-A-C-H**  
+49 (0) 6182 82916-16  
info@newland-id.de

**United Kingdom**  
+44 (0) 1442 212020  
sales@newland-id.co.uk

**France**  
+39 (0) 345 8804096  
france@newland-id.com

**Russia**  
+31 (0) 345 87 00 33  
russia@newland-id.com

**Benelux**  
+31 (0) 345 87 00 33  
benelux@newland-id.com

**Turkey**  
+90 (0) 544 538 40 49  
turkey@newland-id.com

**Ibérica**  
+34 (0) 93 303 74 66  
info@newland-id.es

**Middle East**  
+39 (0) 345 8804096  
middleeast@newland-id.com

**Italy**  
+39 (0) 342 0562227  
italy@newland-id.com

**South Africa**  
Gauteng: +27 (0) 11 553 8010  
Cape Town: +27 (0) 21 9140819  
info@newland-id.co.za

**Nordic & Baltic**  
+46 (0) 70 88 47 767  
nordic@newland-id.com

**Iran**  
+90 (0) 544 538 40 49  
iran@newland-id.com